



OLD060EN

EN 1765 Oil and Fuel Delivery Hose,
20 Bar

Code	ID (mm)	OD (mm)	Wall (mm)	Working Pressure (bar)	Burst Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Max. Length (m)
OLD060EN-102x7	102	116	7	20	60	520	3,57	40
OLD060EN-102x8.5	102	119	8.5	20	60	520	3,73	40
OLD060EN-127x9	127	145	9	20	60	660	5,10	30

Application

Heavy duty discharge hose for transport of mineral oil products and fuel mixtures with aromatic content up to 50%, suitable for offshore applications. This hose is constructed in compliance with ABS / DNV standards.

Temperature

-40°C to +100°C

Features

Durable, long lasting, suitable for assemblies, resistant to aromatic content up to 50%, flame retardant and conductive

Type

Mandrel built

Tube

Oil resistant synthetic rubber compound, black, smooth, anti-static, conductive

Reinforcement

High tensile textile cord fabric, anti-static copper wire

Cover

Blend of synthetic rubber compounds, black, anti-static, conductive, smooth with cloth impression, oil, abrasion, weather, seawater and ozone resistant and flame retardant

Standard/Notice

EN ISO 1765, ABS / DNV

Marking

Embossed or Transfer Label

Standards/Approvals

Comments