



BASKET FILTERS

KEY FEATURES

- ▶ Quick Release
- ▶ Larger filtration area, ensuring minimal pressure loss

DESCRIPTIONS

Fluid Control Barton Firtop Twin Filter Units are available in 6" and 4".

Both models come with frame pockets suitable for Fork Lift/4 points lifting attached to DNV 2.7-1 lifting lugs.



FLUID CONTROL®



BASKET FILTERS



TECHNICAL DATA

6" MODEL

Filter Type	Strainer basket (3mm std. others available by req.)
Operational Pressure	19.2bar (278psi) / -29 to 500C
Piping Diameter (bore)	150mm (6 inch)
Inlet Connection	6" fig 206 male
Outlet Connection	6" fig 150 female

4" MODEL

Filter Type	Strainer basket (3mm std. others available by req.)
Operational Pressure	143 bar (635psi)
Piping Diameter (bore)	100mm (4 inch)
Inlet Connection	4" 300# RF
Outlet Connection	4" 300# RF

WEIGHT & DIMENSIONS

6" MODEL

Maximum Gross Weight	2,000kg
Outer Dimensions (L x W x H)	2,200mm x 1,600mm x 1,300mm

4" MODEL

Maximum Gross Weight	600kg
Outer Dimensions (L x W x H)	1,760mm x 1,360mm x 1,440mm

ADDITIONAL INFORMATION

Year of Construction	2018(6" Model) & 2015(4" Model)
Lifting	Frame pockets suitable for Fork Lift / 4 points lifting Chains attached to DNV 2.7-1 lifting lugs

Fluid Control Service AS

Ljosheimsvegen 1
4050 Sola, Norway

Tel: +47 51 64 49 50
Email: post@fluidcontrol.no



FLUID CONTROL
www.fluidcontrol.no